

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
REGION III  
1650 Arch Street  
Philadelphia, Pennsylvania 19103-2029

**SUBJECT:** Lithium Reanalysis – HW05 18 July 2012  
Dimock, PA

**FROM:** Dawn A. Ioven, toxicologist  
Technical Support Branch (3HS41)

**TO:** Rich Fetzer, OSC  
Eastern Response Branch (3HS31)

Samples initially collected from residential wells in Dimock during Weeks 1 through 4 were recently reanalyzed to achieve lower detection limits for lithium. Findings for HW05 are presented below.

**Lithium**

Lithium was reported in an unfiltered wellhead sample from HW05 at 31 ug/L. The filtered wellhead sample contained lithium at 29.8 ug/L. These concentrations are at or close to lithium's risk-based screening level of 31 ug/L; long-term exposure to the maximum wellhead concentration of lithium (31 ug/L) would generate a Hazard Quotient of 1.0. Under acute exposure conditions, ATSDR has suggested a screening concentration of 1500 ug/L for lithium in drinking water.



*Printed on 100% recycled/recyclable paper with 100% post-consumer fiber and process chlorine free.  
Customer Service Hotline: 1-800-438-2474*